

prisma SOFT max / prisma SMART max

CPAP and APAP therapy: Flexible. Secure. Reliable.

With prisma SOFT max and prisma SMART max, we offer modern, reliable CPAP and APAP therapy featuring integrated connectivity, precise event detection and a high level of patient comfort. The max stands for integrated Bluetooth for data transmission to the prisma APP and thus for modern patient self-management. Equipped with an integrated modem, the max variants also offer the complete telemedical prisma CLOUD connection.

Our Software Solutions

prisma CLOUD



- The telemedical connection for experts and patients. Information updated daily on therapy, fully automated, from anywhere.
- prisma APP
 The prisma APP supports and motivates patients to adhere to treatment.
- prismaTS
 Therapy software for experts. For detailed data analysis and remote settings.

The most important features at a glance

- Two dynamic options for pressure adjustment in APAP mode
- Deep sleep indicator prisma RECOVER for evaluation of sleep quality
- Several convenience functions such as autoSTART, softSTART, pressure relief softPAP
- Detection of periodic breathing, RERA, snoring, hypopnea, apnea and flow limitations
- Reliable differentiation of obstructive apnea from central apnea, thanks to FOT (Forced Osciallatory Technique) ...

... and it's quiet as a whisper for the well-being and comfort of patients and partners.



Accessories

prismaAQUA Humidifier, white Set of 12 pollen filters DC Adapter 12/24 V	WM 229490 WM 29652 WM 24469	Breathing tubes Breathing tube Ø 15 mm Ø 22 mm	WM 29988 WM 24445	Modules prismaPSG PSG module prisma HUB	WM 29690 WM 31660
Medistrom™ Pilot-24 lite Battery	WM 31704	Breathing tube, autoclavable Ø 22 mm WM 24667		Software prismaTS WM 93335	
Transport Bags prismaBAG basic prismaBAG premium	WM 29708 WM 29709	HYBERNITE Superday Heated breathing tube Ø 22 mm	WM 29045	Therapy software complete with USB data c	able

You'll find more information about our therapy solutions, accessories and mask systems at loewensteinmedical.com

Technical data

Product class as per Directive 93/42/EEC	II a	Mean sound pressure level/Operation ISO 80601-2-70	approx. 26.5 dB(A) at 10 hPa	
Dimensions (W x H x D)	170 x 135 x 180 mm	CPAP operating pressure range	4 to 20 hPa	
Weight	ca. 1.34 kg	softSTART adjustable	5 to 45 min	
Temperature range • Operation: • Transport and Storage:	+5 °C to +40 °C -25 °C to +70 °C		4.0 hPa: 150 l/min	
Permitted humidity, operation and storage:	rel. humidity 10% to 95%, no condensation	Highest flow as per ISO 80601-2-70 Mean flow at patient connection port, 22-mm tube	8.0 hPa: 174 l/min 12.0 hPa: 174 l/min 16.0 hPa: 170 l/min 20.0 hPa: 164 l/min	
Pressure range:	700 hPa to 1060 hPa, corresponds to altitude of 3000 m above sea level automatic altitude adjustment	Stability of dynamic pressure (short- term accuracy)at 10 breaths/min.	With 22-mm breathing tube, with and without humidifier: $\Delta p \le 0.3 \text{ hPa}$ $\Delta p \le 0.4 \text{ hPa}$ $\Delta p \le 0.5 \text{ hPa}$ $\Delta p \le 0.5 \text{ hPa}$ $\Delta p \le 0.6 \text{ hPa}$	
Electric rating:	max. 40 VA	as per ISO 80601-2-70 at:		
System interface:	24 V DC max. 5 VA	8.0 hPa 12.0 hPa		
Power consumption in Operation (treatment): bei Bereitschaft (Standby):	240 V 100 V 0.16 A 0.36 A 0.035 A 0.061 A	16.0 hPa 20.0 hPa		
Classification as per EN 60601-1-11		Stability of static pressure (long-term accuracy) ISO 80601-2-70	Δp < 0.25 hPa +/- 3 % of measurement	
 Type of protection from electric shock: Level of protection from electric shock: Protection from damaging 		Pollen filter to 1µm	Filter class E10 ≥ 99.5 %	
ingress of water and solids:	IP21	to 0,3µm	≥ 85 %	

Device description

Ord. Nr.

prisma SOFT max, CPAP therapy device with Bluetooth and modem prisma SMART max, APAP therapy device with Bluetooth and modem

LMT 31970 LMT 31950

Please refer to the current price list.

C€ 0197

Headquarters





Löwenstein Medical Technology Kronsaalsweg 40 22525 Hamburg, Germany T. +49 40 54702-0 F. +49 40 54702-461 info@loewensteinmedical.com Löwenstein Medical Arzbacher Straße 80 56130 Bad Ems, Germany T. +49 2603 9600-0 F. +49 2603 9600-50 info@loewensteinmedical.com

loewensteinmedical.com







